



### DETAILS OF ROCKSHOE

DIA.	$\phi d$	H1	H2	T1	FILLET WELD
$\phi 250$	50	100	300	12	4
$\phi 300$	60	100	300	15	4
$\phi 350$	60	80	330	15	4
$\phi 400$	65	80	330	15	4
$\phi 450$	75	80	330	15	4
$\phi 500$	85	150	450	15	4
$\phi 600$	90	150	500	15	6
$\phi 700$	90	150	500	19	6
$\phi 800$	100	200	600	19	6
$\phi 900$	100	200	600	19	6
$\phi 1000$	120	240	800	19	6

**NOTES:-**

1. SHAFT TO BE JIS SS41 OR EQUIVALENT.
2. ALL MILD STEEL TO BE JIS G3101 SS41 OR EQUIVALENT.
3. ALL DIMENSIONS ARE IN mm.

THIS DRAWING SHALL NOT BE REPRODUCED, COPIED, LOANED OR DISPOSED DIRECTLY OR INDIRECTLY; NOR USED ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED WITHOUT PRIOR WRITTEN CONSENT OF INDUSTRIAL CONCRETE PRODUCTS BERHAD.

PROJECT TITLE :  
**DETAILS OF ROCK SHOE  
(MILD STEEL SHAFT)**

**INDUSTRIAL CONCRETE PRODUCTS BERHAD**  
 2ND FLR, WISMA IJM, JLN YONG SHOOK LIN,  
 P.O BOX 191,  
 46720 PETALING JAYA,  
 SELANGOR DARUL EHSAN, MALAYSIA.  
 TEL : 603-79558888 (13 LINES)  
 FAX : 603-79581111



CHECKED BY :  
 SCALE : N.T.S.  
 DATE : 18/04/2006  
 REVISION :

APPROVED BY :  
 DRAWN BY : MN06  
 FILENAME : RS06-002  
 DWG. NO. : ICP/PJO/RS-06/002